

# Washdown Duty Jet Pump Motors

## Applications:

Industrial pumping applications in wet or humid environments, especially in food and beverage processing facilities in which equipment is cleaned on a regular basis.

## Features:

- Contact lip seal and v-ring slinger on drive end to protect from moisture and contaminants
- White epoxy finish coat
- Sealed-for-life ball bearings
- 300 series stainless steel threaded shaft with opposite drive-end screwdriver slot for ease of mounting to pump assembly
- Stainless steel hardware and nameplate
- Neoprene gaskets with lipped-lid conduit box
- Moisture resistant insulation system
- Rotor coated with epoxy primer for corrosion resistance
- Easily removable condensation drain plugs
- Mobil Polyrex<sup>®</sup> EM moisture resistant grease



**BALDOR**<sup>®</sup>  
A MEMBER OF THE ABB GROUP

**Jet Pump, Three Phase,  
Totally Enclosed Fan Cooled,  
C-face**

**3/4 thru 3 Hp  
NEMA 56J**




Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps
<b>Footless</b>										
3/4	3600	56J	JWDM3463	634	WD	11.84	23	68	208-230/460	1.4
1	3600	56J	JWDM3545	769	WD	11.84	26	72	208-230/460	2
1 1/2	3600	56J	JWDM3550	802	WD	12.47	29	75.5	208-230/460	2.4
2	3600	56J	JWDM3555	905	WD	13.73	41	80	230/460	2.7
3	3600	56J	JWDM3559	1,109	WD	13.73	44	82.5	208-230/460	3.8
<b>Foot Mounted</b>										
3/4	3600	56J	CJWDM3463	639	WD	11.84	24	68	208-230/460	1.4
1	3600	56J	CJWDM3545	774	WD	11.84	27	72	208-230/460	2
1 1/2	3600	56J	CJWDM3550	807	WD	12.47	30	75.5	208-230/460	2.4
2	3600	56J	CJWDM3555	910	WD	13.73	42	80	230/460	2.7
3	3600	56J	CJWDM3559	1,114	WD	13.73	45	82.5	208-230/460	3.8

For additional information on these or any other Baldor products, please visit [www.baldor.com](http://www.baldor.com) or contact your local Baldor•Reliance Sales Representative.



Baldor, the industry leader in washdown motors, also offers a broad line of white washdown and stainless steel encapsulated close-coupled pump motors.



Non-drive end shaft extension is slotted to aid in pump assembly and maintenance.

Shaft extension made of 303 series stainless steel and threaded to meet NEMA 56J dimensions.

**BALDOR**

A MEMBER OF THE ABB GROUP

**Baldor Electric Company**

P.O. Box 2400 • Fort Smith, AR 72902-2400 U.S.A.

Phone (479) 646-4711 • Fax (479) 648-5792

[www.baldor.com](http://www.baldor.com)